







SUGGESTED PCB LAYOUT
TOP VIEW

TOLERANCE (公差) :
0.000 mm $\pm$ 0.075mm
0.00 mm $\pm$ 0.15mm
0.0 mm $\pm$ 0.25mm

Electrical Characteristics :
Insulation Resistance : 500M Ω Min.
Contact Resistance : 50m Ω Max.
Withstand Voltage : 1000 VAC 1 minute.
Current Rating : 1.5A

Material:
Housing: Thermoplastic UL 94V-0
Contact : Selective Gold Plating
Terminal: 0.35mm Thickness Phosphor Bronze
Plated With Gold And Tin In Solder Area.
Shielded: Brass ,Nickel Plating

PART NO : 8 1 8 8 D S - B *** - 0

Positions
Contacts
Housing Color
B : Black
Led Options
Ports
Gold Plated
0 : Gold Flash
1 : 6u"
2 : 15u"
3 : 30u"
4 : 50u"

LED Color Options Table

LED Color Options		LED DASH OPTION
LED 2 (Left)	LED 1 (Right)	
No LED	No LED	0
Yellow	Green	1
No LED	Green	2
Yellow	No LED	3
Green	Yellow	4
Green	Green	5
Yellow	Yellow	6
Orange/Green	Orange/Green	7
Yellow/Green	Yellow/Green	8
Orange/Green	Yellow	9
No LED	Green/Yellow	Z
Green	Orange	A
Orange	Green	B
Green	Red	C
Red	Green	D
Red	Yellow	E
Orange	Orange/Green	F
Orange	Green/Orange	G
Green	No LED	H
Green/Orange	Yellow	K
Green/Yellow	Green/Yellow	P
Green/Red	Yellow/Green	S

SHIELDED RJ45
WITH LED PCB JACK

SoniTexx®